


FEATURES

- | Surface-mounted package
- | Advanced trench cell design
- | Super Trench
- | MSL1



APPLICATION

- | BMS
- | Drones
- | High power inverter system
- | Light electric vehicles



APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

ABSOLUTE MAXIMUM RATINGS

Parameter		Symbol	Value	Unit
Drain-Source Voltage $T_c=25^{\circ}\text{C}$		V_{DS}	150	V
Drain Current (Pulsed) $T_c=25^{\circ}\text{C}$ $V_{GS}=10\text{V}$		I_{DM}^{***}	1016	A
Drain Current (DC)	$T_c=25^{\circ}\text{C}$ $V_{GS}=10\text{V}$	I_D^*	258	A
	$T_c=100^{\circ}\text{C}$ $V_{GS}=10\text{V}$		163	A
Gate-Source Voltage $T_c=25^{\circ}\text{C}$		V_{GS}	± 20	V
Drain power dissipation $T_c=25^{\circ}\text{C}$		P_{tot}	500	W
Junction Temperature		T_J	150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 to 150	$^{\circ}\text{C}$
Single Pulsed Avalanche Energy $L=0.5\text{mH}$, $I_{as}=70\text{A}$, Start $T_J=25^{\circ}\text{C}$		E_{AS}	1225	mJ
Thermal Resistance – Junction to Ambient		$R_{\theta JA}^{**}$	62	$^{\circ}\text{C/W}$
Thermal Resistance- Junction to Case		$R_{\theta JC}^{**}$	0.3	$^{\circ}\text{C/W}$
Continuous-Source Current $T_c=25^{\circ}\text{C}$		I_S	258	A

Notes:

- * Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- ** Surface Mounted on minimum footprint pad area
- *** Limited by bonding wire

ELECTRICAL CHARACTERISTICS (T_A=25°C)

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _{DS} =250μA	150			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _{DS} =250μA	2		4	V
Drain Leakage Current	I _{DSS}	V _{DS} =120V, V _{GS} =0V			1	μA
Gate Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±100	nA
On-State Resistance	R _{DS(on)} ^{Note1}	V _{GS} =10V, I _{DS} =50A		2.8	3.3	mΩ
Diode Characteristics						
Diode Forward Voltage	V _{SD} ^{Note1}	I _{SD} =50A, V _{GS} =0V	0.5		1.2	V
Reverse Recovery Time	t _{rr}	I _{DS} =50A, V _{GS} =0V dI _{SD} /dt=100A/μs		110		nS
Reverse Recovery Charge	Q _{rr}			395		nC
Dynamic Characteristics ^{Note2}						
Input capacitance	C _{iss}	V _{GS} =0V, V _{DS} =75V, Frequency = 1 MHz		12580		pF
Output capacitance	C _{oss}			850		pF
Reverse transfer capacitance	C _{rss}			145		pF
Turn-on Delay Time	t _{d(on)}	V _{DS} =75V, V _{GEN} =10V R _G = 3.0Ω, I _{DS} =50A		22		nS
Turn-on Rise Time	t _r			106		nS
Turn-Off Delay Time	t _{d(off)}			60		nS
Turn-Off Fall Time	t _f			100		nS
Gate Charge Characteristics ^{Note2}						
Total Gate Charge	Q _g	V _{DS} =75V, V _{GS} =10V, I _{DS} =50A		160		nC
Gate-Source Charge	Q _{gs}			51		nC
Gate-Drain Charge	Q _{gd}			21		nC

Notes:

1 : Pulse test ; pulse width ≤ 300μs, duty cycle ≤ 2 %

2 : Guaranteed by design, not subject to production testing

PARAMETER CHARACTERISTIC CURVE

Figure1: Power Capability




Figure2: Current Capability




Figure3: Safe operating Area





Figure 4: Transient Thermal Impedance












**Figure 5: Output Characteristics****Figure 6: On Resistance****Figure 7: Normalized Threshold Voltage vs Junction Temperature****Figure 8: Normalized Breakdown Voltage vs Junction Temperature**

Figure 9: Normalized On Resistance

Figure 10: Diode Forward Current

Figure 11: Capacitance

Figure 12: Gate Charge


TOLL-8L PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.40	0.087	0.094
b	0.70	0.90	0.028	0.035
b1	9.70	9.90	0.382	0.390
b2	0.36	0.55	0.014	0.022
b3	0.05	-	0.002	-
b4	0.30	0.50	0.012	0.020
b5	1.10	1.30	0.043	0.051
b6	3.00	3.20	0.118	0.126
c	0.40	0.60	0.016	0.024
D	10.28	10.55	0.405	0.415
D1	10.98	11.18	0.432	0.440
D2	3.20	3.40	0.126	0.134
D3	7.15		0.281	
D4	3.59		0.141	
D5	3.26		0.128	
e	1.10	1.30	0.043	0.051
E	9.80	10.00	0.386	0.394
E1	7.40	7.60	0.291	0.299
E2	7.40	7.60	0.291	0.299
E3	8.50		0.335	
E4	9.46		0.372	
H	11.50	11.85	0.453	0.466
H1	6.55	6.75	0.258	0.266
K	4.08	4.28	0.161	0.169
L	1.60	2.10	0.063	0.083
L1	0.50	0.90	0.020	0.035
L2	0.50	0.70	0.020	0.028
L3	1.00	1.30	0.040	0.051
L4	0.13	0.33	0.005	0.013
P	2.85	3.15	0.112	0.124
θ	10°REF		0.398°REF	
aaa	0.20		0.008	
ccc	0.20		0.008	
ddd	0.25		0.010	
eee	0.20		0.008	

ORDERING INFORMATION

Part Number	Component Package	Marking	QTY/Reel	QTY/Box
SNM300N15L	TOLL-8L	 300N15 XXXX	2000PCS	14000PCS

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.